



**BLACK HORSE
OFF ROAD®**

TEL: 1-866-XANATOS

INSTALLATION INSTRUCTIONS

MODULAR RUGGED GRILLE GUARD

07-21 TOYOTA TUNDRA


(Excl. 18-21 TSS-P: Pre-collision system & Dynamic radar cruise control)

08-20 TOYOTA SEQUOIA (Excl. 08-20 Platinum)

PART# RU-TOTU07-B/RU-TOTU07-B-KIT/RU-TOTU07-B-PLR


PARTS LIST:

1	Main Body	4	12mm x 32mm OD x 3mm Flat Washers
1	Bottom Tube	4	12mm Lock Washers
1	Driver/Left Side Upright	2	10mm Cam Lever Quick Release Bolts with Special Pivot Washer
1	Passenger/Right Side Upright	12	10mm x 35mm Button Head Allen Screws
1	Driver/Left Brush Guard	28	10mm x 27mm OD x3mm Flat Washers
1	Passenger/Right Brush Guard	14	10-1.5mm Nylon Lock Nuts
2	LED lamp Bracket	10	8mm x 24mm x 2mm Flat Washers
1	20in LED Light	2	8-1.25mm Nylon Lock Nuts
1	Driver/left Frame Mounting Bracket	4	8-1.25mm x 25mm Hex Bolts
1	Passenger/right Frame Mounting Bracket	4	8mm Lock Washers
1	Driver/left Top Frame Bracket	4	8mm x 25mm Button Head Allen Screws
1	Passenger/right Top Frame Bracket	4	12mm Plastic Washers
1	Driver/left Top Bracket	4	10mm Plastic Washers
1	Passenger/right Top Bracket	1	S=5 Wrench
4	12-1.75mm x 35mm Hex Bolts	1	S=6 Wrench
		1	20inch LED Double Row Light




Please Noted:

1. Before you install the Grille Guard on the vehicle, please install the Driver/Left Side Upright, Driver/Left Brush Guard, Passenger/Right Side Upright and Passenger/Right Brush Guard on the main body with the included (2)10mm Cam Lever Quick Release Bolts with Special Pivot Washer, (8) 10mm x 35mm Button Head Allen Screws, (10) 10-1.5mm Nylon Lock Nuts and (20) 10mm x 27mm OD x3mm Flat Washers. Attach the Bottom Tube to the Upright with the included (4) 10mm x 35mm Button Head Allen Screws, (4) 10-1.5mm Nylon Lock Nuts and (8) 10mm x 27mm OD x3mm Flat Washers.



2. Before you install the LED Lamp on the main body please install the LED Lamp Bracket first.
3. If you are not going to install a LED Lamp, the LED Lamp Bracket installation is unnecessary. For main body installation follow the instruction as below.



IMPORTANT: The Grille Guard is designed to tilt forward to clear the attached grille on 2007-13 Tundra, 08-14 Sequoia models. To tilt the Grille Guard, the Quick Release Bolts on the Top Brackets must be released and the upper bolts on both Mounting Brackets may need to be loosened slightly. Make sure that all hardware is fully tightened after closing the hood. Carefully read Page 9-10, "Opening and Closing of Hood," before installing the Grille Guard.

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION. MAY INTERFERE WITH FRONT MOUNTED SENSORS. NOT RECOMMENDED FOR VEHICLES WITH OPTIONAL "ACTIVE" LASER GUIDED CRUISE CONTROL SYSTEMS. CUTTING MAY BE REQUIRED.**
2. Start installation at the front of the vehicle.
07-13 Tundra, 08-14 Sequoia models: Open the hood. Top Brackets can either be installed from above or below front bumper depending on model, accessories and year, **(Figure 1A & 1B)**.
2014-on Tundra models: Top Brackets must be installed from below front bumper, **(Figure 1B)**.
3. Locate the passenger side bumper bracket bolted to the end of the frame. Access the bracket through the gap between the front bumper and the radiator or from below the bumper above the tow hook, **(Figure 1B)**. If installing from below, remove the hardware attaching the bumper cover to the cross member to access the end of the frame and bracket, **(Figure 2)**.
4. Select the passenger /right Top Frame Bracket, **(Figure 3A)**. Remove the top (2) factory hex nuts on the outside of the frame, attaching the passenger/right factory bumper bracket to the end of the frame, **(Figure 3B)**.
5. Slide the L-shaped Bracket over the top of the bumper bracket and down and over the (2) threaded studs, **(Figure 4)**. If installing from below, carefully pull the bottom of the bumper cover outward and slide the Bracket up and in position. Reuse the factory hex nuts to attach the Top Bracket to the bumper bracket. Snug but do not fully tighten the (2) hex nuts at this time.
6. Repeat **Steps 3—5** to install the driver side Top Frame Bracket. **IMPORTANT:** Installation will require removal or cutting of plastic air deflector, if equipped, attached to the back of the lower grille, **(Figures 5A & 5B)**. **NOTE:** Depending year and model, it may be necessary or easier to remove bumper cover to remove the air deflector from the back of lower grille insert.
7. From under the front of the vehicle, remove the (2) factory tow hooks and set aside, **(Figures 6 & 7)**. Select the passenger side Frame Mounting Bracket, **(Figure 8A)**.
Vehicles with small tow hook: Line up the holes in the tow hook with the slots in the Bracket. Bolt the tow hook and Bracket to the bottom of the frame using the factory tow hook bolts, **(Figure 8B)**.
Vehicles with large tow hooks: Bolt the passenger/right side Frame Mounting Bracket directly to the bottom of the frame with the two factory hex bolts. **NOTE:** Large tow hooks cannot be reinstalled, **(Figure 7)**.
8. Repeat **Step 7** to install the driver/left side Frame Mounting Bracket. Leave hardware loose at this time.
9. Select the passenger side Top Bracket, **(Figure 9A)**. Apply the included Adhesive Backed Foam Tape to the Bracket as needed to protect the grille opening from contact with the Bracket.
10. Slide the Top Bracket in through the opening in the bumper, **(Figure 9B)**. Line up the (2) holes in the Bracket with the previously installed Frame Bracket, **(Figure 10A)**. Bolt the Top Bracket to the top of the Frame Bracket with (2) 8-1.25mm x 25mm Hex Bolts, (2) 8mm x 24mm x 2mm Flat Washers and (2) 8mm Lock Washers, **(Figure 10B)**. Leave hardware loose at this time.
11. Repeat **Steps 9 & 10** to install the driver side Top Bracket.
12. With assistance, place the Grille Guard face down on a clean surface in front of the vehicle. Position the mounting tabs on the Grille Guard up to the outside of the passenger side Frame Mounting Bracket. Line up the lower hole in the Bracket with the lower hole in the Grille Guard.
13. Insert (2) 12mm Plastic Washer between the Mounting Bracket and the Grille Guard. Line up the Grille Guard, Washer and Bracket and bolt together with the included (2) 12-1.75mm x 35mm Hex Bolts, (2) 12mm Lock Washers and (2) 12mm x 32mm OD x 3mm Flat Washers, **(Figure 11)**.
14. Repeat **Steps 12—13** to attach the driver side mounting tab to the Bracket. Leave hardware loose.

15. Use the (2) previously installed 12mm Hex Bolts as a hinge. With assistance, carefully rotate the Grille Guard up to the vehicle, **(Figure 11)**. Line up the two remaining holes in the Mounting Brackets with the holes in the Grille Guard. Repeat **Steps 13 & 14** to attach the Grille Guard to the Brackets, **(Figure 12)**. Snug but do not tighten hardware at this time.
16. Next, move to the passenger side Top Bracket installed in **Steps 9 & 10**. Line up the long slot in the Top Bracket with the slot in the Grille Guard upright, **(Figure 13)**. Insert (1) 10mm Cam Lever Quick Release Bolts with Special Pivot Washer and (1) 10mm x 27mm OD x3mm Flat Washer through the Grille Guard. Thread (1) 10mm Plastic Washer part way onto the threads. Slide the Top Bracket over the Quick Release. Thread (1) 10mm Plastic Washer, (to protect the finish on the Top Bracket), (1) 10mm x 27mm OD x3mm Flat Washer and (1) 10-1.5mm Nylon Lock Nut, **(Figure 13)**, onto the Quick Release. Do not fully tighten hardware at this time.
17. Repeat **Step 16** to attach the driver side Top Bracket to the Grille Guard.
18. Release/loosen the levers on the Quick Release Bolts, **(Figure 13)**, and pull the Grille Guard away from the vehicle to the "open" position, **(Figure 15)**. **NOTE:** It may be necessary to slightly loosen the top (2) 12mm Hex Bolts on the Frame Mounting Brackets to move the Grille Guard, **(Figure 16)**. Center and level the Grille Guard and tighten all hardware including the Frame Mounting Brackets.
19. Adjust the Quick Release Bolt clamping pressure by loosening or tightening the 10-1.5mm Nylon Lock Nuts. See **Steps 24—29** for more information. **NOTE:** Tilt feature only required on 07-13 Tundra and 08-14 Sequoia models. 2014-on.
20. Slowly close the hood and check for clearance. Release both Quick Release bolts. Push the Grille Guard into the "closed" position. If needed, loosen the upper bolt on each Frame Mounting Bracket, **(Figure 16)**. **WARNING!** Do not completely loosen bolts or damage to the truck or Grille Guard may occur.
21. Push the Grille Guard back towards the vehicle and fully tighten all hardware, **(Figure 17 & 18)**. Reattach the bottom of the bumper cover with the factory hardware, **(Figure 2)**.
22. Do periodic inspections to the installation to make sure that all hardware is secure and tight.
23. Before you install the LED Lamp on the main body , line up the LED lamp Bracket and 20in LED together with the included (2) 8mm x 25mm Button Head Allen Screws and (2) 8mm x 24mm x 2mm Flat Washers, **(Figure 19)**.

Opening and closing the hood-required for 2007-13 models only


24. Lift the levers on the Quick Release bolts to release the clamping pressure, **(Figure 14)**. Pull the Grille Guard out and away from the vehicle to the "open" position, **(Figure 15)**. **NOTE:** If the Grille Guard does not pivot to "open" position, **slightly loosen the 12mm upper hex bolt on each Mounting Bracket, (Figure 16)**. **WARNING!** Do not completely loosen bolts or damage to the truck may occur.
25. Carefully pull on the Grille Guard until it is fully extended away from the vehicle, **(Figure 15)**.
26. Pull the hood release and slowly open the hood.
27. **IMPORTANT!** Before closing the hood, always make sure that the Grille Guard is in the full open position and away from the vehicle. Pull on the Grille Guard to verify that it is fully extended away from the vehicle and slowly close the hood, **(Figure 15)**.
28. Once the hood is completely closed, push the Grille Guard back to its "closed," upright position and tighten all hardware on the Grille Guard, **(Figure 17)**. Push down on the Quick Release lever to tighten, **(Figure 18)**. No tools are required to close the Quick Release levers. It will require some effort to open and close by hand when properly adjusted. Loosen or tighten the 10mm Nylon Lock Nut on the Quick Release bolt to adjust the clamping pressure.
29. Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.


For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Grille Guard.

For gloss black finishes: Mild soap may be used to clean the Grille Guard.

Passenger/right Side Installation Pictured




(Fig 1A) 07-13 Tundra bumper bracket location pictured from above



(Fig 1B) 2014 passenger side pictured from below




(Fig 2) If necessary, temporarily remove bumper cover hardware to access bumper bracket (passenger/right side pictured from below)



(Fig 3A) Reuse the (2) factory hex nuts to attach the passenger/right Top Bracket to the factory bumper bracket


Passenger/right Side Installation Pictured

Remove (2) top factory hex nuts
on outside of bumper bracket



(Fig 3B) Passenger side Top Bracket pictured installed over bumper bracket. Pictured from below

Passenger side
top bracket



(Fig 4) Reuse factory hex nuts to secure Top Bracket to end of frame. Remove tow hooks



(Fig 5A) Remove or cut air deflector from behind lower grille opening in bumper

Threaded holes for
factory tow hook






Fig 6




(Fig 5B) Air deflector on driver side pictured from behind bumper. Note: Not included on all models


Passenger/right Side Installation Pictured




(Fig 7) The heavy duty factory tow hooks cannot be reinstalled.




(Fig 8A) Passenger side Frame Mounting Bracket



(Fig 8B) Install Frame Bracket with factory tow hook bolts. Small tow hook pictured FOR EXAMPLE ONLY




(Fig 9B) Insert Top Bracket into opening in bumper (Grille guard pictured installed for reference only do not install at this time)



(Fig 9A) Passenger side Top Bracket

Passenger/right Side Installation Pictured




(Fig 10A) Passenger side Top Bracket and Top Frame Bracket illustrated

Attach Top Bracket to Frame Bracket with:


- (2) 8-1.25mm x 25mm Hex Bolts
- (2) 8mm x 24mm x 2mm Flat Washers
- (2) 8mm Lock Washers

- (2) 8mm x 25mm Hex Bolts
- (2) 8mm Lock Washers
- (2) 8mm Flat Washers



(Fig 10B) Driver side 07-13 pictured from above

- (2) 12-1.75mm x 35mm Hex Bolts
- (2) 12mm Lock Washers
- (2) 12mm x 32mm OD x 3mm Flat Washers
- (2) 12mm Plastic Washers (between Grille Guard and Bracket)




(Fig 11) Insert a Plastic Washer between the Grille Guard and the Frame Mounting Bracket on each 12mm Hex Bolt




(Fig 12) Attach the Grille Guard to the Brackets

Passenger/right Side Installation Pictured



(Fig 13) Insert a 10mm Plastic Washer between the Grille Guard and the Top Bracket and under the Flat Washer on each Quick Release Bolt. (2) Plastic Washers are required for each Quick Release installation



(Fig 14) Pull handle to "open" Quick Release




Fig 16

Passenger/right Side Installation Pictured




(Fig 17) Push Grille Guard back to the "closed" position



(Fig 18) Quick Release in "closed" position

- (2) 8mm x 25mm Button Head Allen Screws
- (2) 8mm x 24mm x 2mm Flat Washers



(Fig 19)