

# Installation Instructions

## ASTC24

[Fits: Tesla Cyber Truck]

**Thank you for your purchase! Please contact us for any issues!**

### Accessories List:

- 4 PCS Self-Tapping Screws
- 4 PCS Hex Acorn Nuts

### Tools Needed:

- Phillips Screwdriver
- Punch Needle
- Hex Socket Driver

**Note 1** Before beginning installation, ensure all accessories are included. Contact us if anything is missing.

**Note 2** Set the password with the lid door **OPEN**; do not close the door of the safe vault during password setup.

### 1. Prepare for Installation:

- Remove all items from the center console.

### 2. Install Brackets and Top Panel:

- Place the left and right side brackets into the armrest box.
- Position the top panel over the brackets, aligning the screw areas with the reserved holes in the brackets.

### 3. Secure Top Panel:

- With the lid open, install the hex acorn nuts onto the screw areas on the panel.
- Use the hex socket driver to tighten the hex acorn nuts. Be careful not to over-tighten them.

### 4. Attach Side Brackets:

- Using the punch needle, pierce holes through the reserved holes on the left and right side brackets into the side of the console box.
- Utilize a Phillips screwdriver to secure the screws into the pierced holes. Avoid over-tightening to prevent damage to the console box.

### 5. Completion and Safety:

- Once installation is complete, enjoy using the product.
- If you require any assistance, please do not hesitate to contact us.